

LPTMXHHD_600TVL

- ★Vandalproof Mini PTZ Speed Dome camera
- ★Pan range: 0°~360° Continue (Not 355°)
- ★Tilt range: 0°~90° Flip
- ★Pan Speed: Max 50°/sec Preset: 16
- ★Weatherproof Outdoor IP66
- ★RS485, Pelco D/P supported
- ★4-9mm dynamic varifocal lens (standard)
- ★5-15mm dynamic varifocal lens (optional)



Model	LPTMXSHE	LPTMXSHR	LPTMXSHD	LPTMXHHD	LPTMXSL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SHARP ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR	420TV Lines Low Illumination
CCD+DSP	ICX673AK+Effio-e	ICX639BK+RJ10	ICX639BK+NVP2040	RJ2365CA+NVP2040	ICX633BK+CXD3142
Pixels	PAL:1020(H)×596 (V), NTSC:1020(H)× 508(V)	PAL:795(H)×596(V), NTSC:811(H)×508 (V)	PAL:795(H)×596(V), NTSC:811(H)×508(V)	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
TV System	PAL/NTSC				
Lens	4-9mm dynamic varifocal lens (standard) / 5-15mm dynamic varifocal lens (optional)				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0			0.0005Lux/F2.0	
S/N Ratio	≥65dB (AGC OFF)		≥54dB (AGC OFF)		≥48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec				
Operation Temperature	-10°C ~ +50°C RH95% Max				
Storage Temperature	-20°C ~ +60°C RH95% Max				
White Balance	Auto				
Power Source	DC12V 800mA				
Dimension	121x177mm				
Weight	2.8Kg				