

LCDC

Plastic Dome Camera
 SONY/SHARP Color CCD
 3-Axis bracket built-in
 Lens: 3.6mm Board lens
 OSD Menu controlled by cable button
 Dimension: \varnothing 120 x 82(H) mm Weight:520g



Model	LCDCSHE	LCDCSHR	LCDCSHD	LCDCSHD	LCDCSHD	LCDCSL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SHARP ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense- up	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR	Color 1/3" SONY 600TVL, Low Illumination, DWDR, OSD, DNR	420TV Lines Low Illumination
CCD+DSP	ICX673AK+Effio-e	ICX639BK+RJ10	ICX639BK+NVP2040	ICX639BK+NVP2040	RJ2365CA+NVP2040	ICX633BK+CXD3142
Pixels	PAL:1020(H)×596(V), NTSC:1020(H)×508(V)	PAL:795(H)×596(V), NTSC:811(H)×508(V)	PAL:795(H)×596(V), NTSC:811(H)×508(V)	PAL:795(H)×596(V), NTSC:811(H)×508(V)	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:500(H)×582(V), NTSC:510(H)×492(V)
TV System			PAL/NTSC			
Lens			3.6mm Board Lens			
Sync System			Internal			
Usable Illumination			0.001Lux/F2.0			0.0005Lux/F2.0
S/N Ratio	≥65dB (AGC OFF)		≥54dB (AGC OFF)			≥48dB (AGC OFF)
Gamma Correction			0.45			
Video Out			Composite Signal (1.0Vp-p, 75Ω)			
Scanning System			PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time			Auto:PAL 1/50-1/100, 000Sec;NTSC 1/60-1/100, 000Sec			
Operation Temperature			-10°C ~ +50°C RH95% Max			
Storage Temperature			-20°C ~ +60°C RH95% Max			
White Balance			Auto			
Power Source			DC12V 150mA			
Dimension			\varnothing 120 x 82(H) mm			
Weight			520g			